

AGROTRON X.



AGROTRON X 720




AGROTRON X		720
ENGINE		
Emissions		Stage III A
Manufacturer		Deutz TCD 2013 L06 4V DCR
Deutz Common Rail		●
Cylinders/Displacement	n°/cc	6/7146
Turbo intercooler		●
Max. power (2000/25/EC)	kW/HP	202/275
Power at rated engine speed (2000/25/EC)	kW/HP	198/269
Max. torque	Nm	1035
Electronic engine governor		●
Air filter with dust ejector		●
Fuel tank capacity	litres	560
TRANSMISSION		
Speeds with creeper	n°	40+40
Powershift steps	n°	4
Minimum speed with creeper	km/h	0.48
Max. speed	km/h	50*
Automatic Powershift (APS)		●
Comfort Clutch		●
PTO		
Rear PTO 540ECO/1000		●
Front PTO 1000		○
Auto PTO		●
AXLES AND BRAKES		
Suspended front axle		○
ASM system		●
Wet rear disc brakes		●
Hydrostatic steering with independent pump		●
HYDRAULIC SYSTEM AND LIFT		
Electronic rear lift		●
Rear lifting capacity	kg	10500
Front lifting capacity	kg	5100
Load Sensing pump flow (std/opt)	l/min	120/160
Electronically operated spool valves		●
Rear auxiliary spool valves	n°	4
Flow regulator and timer		●
DRIVING POSITION		
Multifunction armrest		●
Pneumatic cab suspension		●
WorkMonitor		●
Performance Monitor		●
Comfortip		●
Air conditioning		●
DIMENSION AND WEIGHT		
Standard front tyres		600/70 R30
Standard rear tyres		710/70 R38
Wheelbase	mm	3095
Length (min.-max.)	mm	5209-5399
Height (min.-max.)	mm	3625-3270
Width (min.-max.)	mm	2500-2749
Ground clearance (min.-max.)	mm	445-625
Total unladen weight (min.-max.)	kg	8753-9995

● = standard ○ = optional – = not available * Measured at 610 mm ISO point

The technical data and pictures are guideline only. Committed to delivering a product more and more in line with your needs, DEUTZ-FAHR reserves the right to update the specifications of its machines at any time without notice.

DEALER

To discover more please contact your dealer
or visit deutz-fahr.com.
DEUTZ-FAHR is a brand of  SDF

