



Versatile, easy to maintain and use.
Available even without roll bar.

DEUTZ-FAHR
AGROFARM C 80-90-100



TECHNICAL DATA		AGROFARM C		
		80	90	100
ENGINE				
Emissions		Tier2	Tier2	Tier2
Manufacturer		SDF 1000.4 W	SDF 1000.4 WT	SDF 1000.4 WT
Cylinders/Capacity	No./cc	4/4,000	4/4,000	4/4,000
Naturally aspirated		•	-	-
Turbocharged intake		-	•	•
Max. homologated power (2000/25/EC)	kW/hp	54.7/74	64.6/88	69.6/95
Rated speed	rpm	2350	2350	2350
Max. torque	Nm	260	350	375
Engine control mechanical		•	•	•
Cyclone pre-filter		o	o	o
Cooling liquid		•	•	•
Under-hood silencer with side exhaust		o	o	o
Fuel tank capacity	litres	50	85	85
MECHANICAL GEARBOX				
Synchronised		•	•	•
Number of speeds	n°	12+12	12+12	12+12
Number of speeds, 4 gears with supercreeper gear	n°	16+16	16+16	16+16
Number of speeds, 5 gears with supercreeper gear	n°	20+20	20+20	20+20
Min. speed with supercreeper gear	km/h	0.18/1.61	0.18/1.61	0.18/1.61
Max. speed	km/h	30/40	30/40	30/40
Hydraulically operated mechanical clutch		•	•	•
REAR PTO				
Mechanically operated multi-plate hydraulic clutch		•	•	•
Mechanical engagement		•	•	•
PTO 540/1000		•	•	•
PTO 540/1000 + Ground speed PTO		o	o	o
FRONT AND REAR AXLE				
Four wheel drive mechanically engaged		•	•	•
Mechanically operated differential lock		•	•	•
Steering angle/turning circle 2WD	degrees/mm	70°/3,350	70°/3,350	70°/3,350
Steering angle/turning circle 4WD	degrees/mm	50°/4,150	50°/4,500	50°/4,500
BRAKES				
Braking system with wet brake discs		•	•	•
Mechanical hand brake		•	•	•
STEERING				
Hydrostatic steering with independent pump		•	•	•
HITCH				
Category		II	II	II
Mechanical rear hitch		•	•	•
Rear hitch capacity	kg	3,450	3,084	3,084
Rear hitch capacity (opt)	kg	-	4,760	4,760
HYDRAULIC SYSTEM				
Pump output (std)	l/min	34.2	42.2	42.2
Pump output (opt)	l/min	55	55	55
Open-centre hydraulic system		•	•	•
Mechanical auxiliary valve engagement		•	•	•
Rear auxiliary hydraulic valves	No.	1/2	2/3	2/3
DRIVER AREA				
Side control levers		•	•	•
Platform variant with a ROPS roll frame		•	•	•
Driver seat with mechanical suspension		•	•	•
Analogue instrumentation		•	•	•
DIMENSIONS AND WEIGHTS				
Standard rear tyres		420/85R30"	460/85R34"	460/85R34"
Max. length	mm	3630	3635	3635
Width	mm	2430	2290	2290
Wheelbase (4WD/2WD)	mm	2247/2297	2297/2320	2297/2320
Front track	mm	1524/1640	1524/1640	1524/1640
Rear track	mm	1500-1600	1500-1600	1500-1600
Max. height with roll bar	mm	2200	2278	2278
Weight (4WD/2WD)	kg	2775/2450	3275/2870	3275/2870
Maximum permissible load (4WD/2WD)	kg	4900/4400	5450/4850	5450/4850

STD • OPT o - Not available

Dealer



Deutz-Fahr recommends original lubricants and coolants.

DEUTZ-FAHR IS A BRAND OF SDF
deutz-fahr.com




Versatile, easy to maintain and use.
Available even without ROPS

DEUTZ-FAHR
AGROFARM C



TECHNICAL DATA		AGROFARM C		
		75	85	95
ENGINE				
Emissions		Tier1	Tier1	Tier1
Manufacturer		SDF 1000.4 W	SDF 1000.4 W	SDF 1000.4 WT
Cylinders/Capacity	No./cc	4/4,000	4/4,000	4/4,000
Natural aspiration		●	●	●
Turbocharged aspiration		-	-	●
Max. homologated power (ECE R 120)	kW/hp	54,5/74	62/84	69/95
Max. engine speed (rated)	rpm	2,350	2,500	2,500
Max. torque	Nm	256	283	321
Engine control mechanical		●	●	●
Cyclone prefilter		○	○	○
Cooling liquid		●	●	●
Under-hood silencer with side exhaust		○	○	○
Fuel tank capacity	litres	50	85	85
MECHANICAL GEARBOX				
Synchromesh		●	●	●
Number of speeds	n°	12+12	12+12	12+12
Number of speeds, 4 gears with supercreeper gear	n°	16+16	16+16	16+16
Number of speeds, 5 gears with supercreeper gear	n°	20+20	20+20	20+20
Min. speed with supercreeper gear	km/h	0.18/1.61	0.18/1.61	0.18/1.61
Max. speed	km/h	30/40	30/40	30/40
Mechanical dry clutch, single		●	●	●
REAR PTO				
Mechanical dry clutch, single		●	●	●
Mechanical engagement		●	●	●
PTO 540/1,000		●	●	●
FRONT AND REAR AXLE				
Front wheel drive mechanically engaged (only 4WD versions)		●	●	●
Mechanically operated differential lock		●	●	●
Steering angle/turning circle 2WD	degrees/mm	70°/3,350	70°/3,350	70°/3,350
Steering angle/turning circle 4WD	degrees/mm	50°/4,150	50°/4,500	50°/4,500
BRAKES				
Braking system with wet brake discs		●	●	●
Mechanical parking brake		●	●	●
STEERING				
Hydrostatic steering with independent pump		●	●	●
HITCH				
Category		II	II	II
Rear hitch mechanical		●	●	●
Rear hitch lift capacity	kg	3,450	3,084	3,084
Rear witch lift capacity (opt)	kg	-	4,760	4,760
HYDRAULIC SYSTEM				
Pump output (std)	l/min	34,2	42,2	42,2
Pump output (opt)	l/m	55	55	55
Open-centre hydraulic system		●	●	●
Mechanical distributor engagement		●	●	●
Rear auxiliary hydraulic distributors	No. of ways	2/4	4/6	4/6
DRIVING POSITION				
Side control levers		●	●	●
Platform with ROPS		●	●	●
Driver seat with mechanical suspension		●	●	●
Instrumentation analogue		●	●	●
DIMENSIONS AND WEIGHTS				
Standard rear tyres		420/85R30"	460/85R34"	460/85R34"
Max. length	mm	3,630	3,635	3,635
Width	mm	2,430	2,290	2,290
Wheelbase (4WD/2WD)	mm	2,247/2,270	2,297/2,320	2,297/2,320
Front track	mm	1,524/1,640	1,524/1,640	1,524/1,640
Rear track	mm	1,500-1,600	1,500-1,600	1,500-1,600
Max height with roll bar	mm	2,200	2,278	2,278
Weight (4WD/2WD)	kg	2,775/2,450	3,275/2,870	3,275/2,870
Maximum load capacity (4WD/2WD)	kg	4,900/4,400	5,450/4,850	5,450/4,850

STD ● OPT ○ - Not available

Dealer



Deutz-Fahr recommends original lubricants and coolants.

DEUTZ-FAHR is a brand of SDF
deutz-fahr.com

